

SIMATIC S7-1500, DIGITAL OUTPUT MODULE DQ 8 X 230VAC,2A ST,TRIAC; 8 CHANNELS IN GROUPS OF 1, 2A PER GROUP; SUBSTITUTE VALUE



Figure similar

General information	
Product type designation	DQ 8x230 V AC/2A ST (triac)
HW functional status	FS01
Firmware version	V2.0.0
<ul style="list-style-type: none"> FW update possible 	Yes
Product function	
<ul style="list-style-type: none"> I&M data 	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> STEP 7 TIA Portal configurable/integrated as of version 	V12 / V12
<ul style="list-style-type: none"> STEP 7 configurable/integrated as of version 	V5.5 SP3 / -
<ul style="list-style-type: none"> PROFIBUS as of GSD version/GSD revision 	V1.0 / V5.1
<ul style="list-style-type: none"> PROFINET as of GSD version/GSD revision 	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> DQ 	Yes
<ul style="list-style-type: none"> DQ with energy-saving function 	No
<ul style="list-style-type: none"> PWM 	No

• Oversampling	No
• MSO	Yes
Output voltage	
Rated value (AC)	230 V; 120/230V AC, 50/60 Hz
Power	
Power available from the backplane bus	0.9 W
Power loss	
Power loss, typ.	10.8 W
Digital outputs	
Number of digital outputs	8
Current-sourcing	Yes
Short-circuit protection	No
Switching capacity of the outputs	
• with resistive load, max.	2 A
• on lamp load, max.	50 W
Output voltage	
• for signal "1", min.	L1 (-1.5 V) at maximum output current; L1 (-8.5 V) at minimum output current
Output current	
• for signal "1" rated value	2 A
• for signal "1" permissible range, min.	10 mA
• for signal "1" permissible range, max.	15 A; max. 1 AC cycle
• for signal "0" residual current, max.	2 mA
Output delay with resistive load	
• "0" to "1", max.	1 AC cycle
• "1" to "0", max.	1 AC cycle
Parallel switching of two outputs	
• for logic links	No
• for uprating	No
• for redundant control of a load	Yes
Switching frequency	
• with resistive load, max.	10 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs	
• Current per channel, max.	2 A; see additional description in the manual
• Current per group, max.	2 A; see additional description in the manual
• Current per module, max.	10 A; see additional description in the manual
Triac outputs	
• Size of motor starters according to NEMA, max.	5
Cable length	

- shielded, max. 1 000 m
- unshielded, max. 600 m

Isochronous mode

Isochronous operation (application synchronized up to terminal) No

Interrupts/diagnostics/status information

Diagnostics function No

Substitute values connectable Yes

Alarms

- Diagnostic alarm No

Diagnostic messages

- Monitoring the supply voltage No
- Wire-break No
- Short-circuit No

Diagnostics indication LED

- RUN LED Yes; Green LED
- ERROR LED Yes; Red LED
- Monitoring of the supply voltage (PWR-LED) No
- Channel status display Yes; Green LED
- for channel diagnostics No
- for module diagnostics Yes; Red LED

Potential separation

Potential separation channels

- between the channels Yes
- between the channels, in groups of 1
- between the channels and backplane bus Yes
- Between the channels and load voltage L1 Yes

Permissible potential difference

between different circuits 250 V AC between the channels and the backplane bus; 500 V AC between the channels

Isolation

Isolation tested with 3 100 V DC

Ambient conditions

Ambient temperature during operation

- horizontal installation, min. 0 °C
- horizontal installation, max. 60 °C
- vertical installation, min. 0 °C
- vertical installation, max. 40 °C

Decentralized operation

Prioritized startup	Yes
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	290 g
last modified:	12/07/2016