

SIMATIC S7-1500 DIGITAL IN-/OUTPUT MODULE, DI16x 24VDC BA, 16 CHANNELS IN GROUPS OF 16, INPUT DELAY TYP. 3.2MS; INPUT TYPE 3 (IEC 61131), DQ 16X24VDC/0.5A BA; 16 CHANNELS IN GROUPS OF 8; 4A PER GROUP INCL. FRONT CONNECTOR PUSH-IN



General information	
Product type designation	DI 16x24VDC / DQ16x24VDC/0.5A BA
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Counter</li> </ul>	No
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No
<ul style="list-style-type: none"> <li>PWM</li> </ul>	No

• Oversampling	No
• MSI	Yes
• MSO	Yes

#### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 7 A per group

#### Input current

Current consumption, max.	30 mA
---------------------------	-------

#### Output voltage

Rated value (DC)	24 V
------------------	------

#### Power

Power available from the backplane bus	1.1 W
----------------------------------------	-------

#### Power loss

Power loss, typ.	3.45 W
------------------	--------

#### Digital inputs

Number of digital inputs	16
Digital inputs, parameterizable	No
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 3	Yes

#### Input voltage

• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-30 to +5V
• for signal "1"	+11 to +30V

#### Input current

• for signal "1", typ.	2.7 mA
------------------------	--------

#### Input delay (for rated value of input voltage)

##### for standard inputs

— parameterizable	No
— at "0" to "1", min.	3 ms
— at "0" to "1", max.	4 ms
— at "1" to "0", min.	3 ms
— at "1" to "0", max.	4 ms

##### for interrupt inputs

— parameterizable	No
-------------------	----

#### Cable length

• shielded, max.	1 000 m
------------------	---------

- unshielded, max. 600 m

## Digital outputs

Number of digital outputs	16
Current-sourcing	Yes
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>• Response threshold, typ.</li> </ul>	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	5 W
<b>Load resistance range</b>	
<ul style="list-style-type: none"> <li>• lower limit</li> </ul>	48 Ω
<ul style="list-style-type: none"> <li>• upper limit</li> </ul>	12 kΩ
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L+ (-0.8 V)
<b>Output current</b>	
<ul style="list-style-type: none"> <li>• for signal "1" rated value</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• for signal "1" permissible range, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• for signal "0" residual current, max.</li> </ul>	0.5 mA
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> </ul>	100 μs
<ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>	500 μs
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for logic links</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>• for redundant control of a load</li> </ul>	Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>• with inductive load, max.</li> </ul>	0.5 Hz
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	10 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>• Current per channel, max.</li> </ul>	0.5 A; see additional description in the manual
<ul style="list-style-type: none"> <li>• Current per group, max.</li> </ul>	4 A; see additional description in the manual
<ul style="list-style-type: none"> <li>• Current per module, max.</li> </ul>	8 A; see additional description in the manual
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>• unshielded, max.</li> </ul>	600 m

## Encoder

<b>Connectable encoders</b>	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes

— permissible quiescent current (2-wire sensor), max.

1.5 mA

### Isochronous mode

Isochronous operation (application synchronized up to terminal)

No

### Interrupts/diagnostics/status information

Diagnostics function

No

Substitute values connectable

No

### Alarms

- Diagnostic alarm
- Hardware interrupt

No

No

### Diagnostic messages

- Monitoring the supply voltage
- Wire-break
- Short-circuit
- Group error

No

No

No

No

### Diagnostics indication LED

- RUN LED
- ERROR LED
- Monitoring of the supply voltage (PWR-LED)
- Channel status display
- for channel diagnostics
- for module diagnostics

Yes; Green LED

Yes; Red LED

Yes; Green LED

Yes; Green LED

No

No

### Potential separation

#### Potential separation channels

- between the channels
- between the channels, in groups of
- between the channels and backplane bus

No

8

Yes

### Isolation

Isolation tested with

707 V DC (type test)

### Ambient conditions

#### Ambient temperature during operation

- horizontal installation, min.
- horizontal installation, max.
- vertical installation, min.
- vertical installation, max.

0 °C

60 °C

0 °C

40 °C

### Decentralized operation

Prioritized startup

Yes

### Dimensions

Width	25 mm
Height	147 mm
Depth	129 mm

#### Weights

Weight, approx.	280 g
-----------------	-------

#### Other

Note: Supplied incl. 40-pole push-in front connectors

**last modified:** 12/12/2016