

SIMATIC S7, TS ADAPTER IE BASIC FOR SIMATIC
TELESERVICE, CONNECTION ON ETHERNET, POWER SUPPLY
EXT. 24V,



General information

Engineering with

- | | |
|---|------|
| • STEP 7 TIA Portal configurable/integrated as of version | V11 |
| • STEP 7 configurable/integrated as of version | V5.4 |

Installation type/mounting

Rail mounting possible	Yes
Wall mounting/direct mounting possible	Yes

Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption, typ.	50 mA; Incl. TS Module Modem
Current consumption, max.	100 mA
Inrush current, max.	5.8 A

Interfaces

Number of industrial Ethernet interfaces	1
Industrial Ethernet	
<ul style="list-style-type: none"> • Industrial Ethernet interface <li style="padding-left: 20px;">— 100 Mbps <li style="padding-left: 20px;">— 1000 Mbps 	1 x Ethernet (RJ45) Yes No
Dimensions	
Width	30 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	100 g
last modified:	10/28/2016