SIEMENS

Data sheet

6GK7543-1AX00-0XE0

Product type designation

CP 1543-1

COMMUNICATION PROCESSOR CP 1543-1 FOR CONNECTING SIMATIC S7-1500 TO INDUSTRIAL ETHERNET; TCP/IP, ISO, UDP, S7-COMMUNICATION, IP-BROADCAST/ MULTICAST, Security (VPN, Firewall), DIAGNOSIS SNMPV1/V3, DHCP, FTP CLIENT/SERVER, E-MAIL, IPV4/IPV6, CLOCK SYNCHRONISATION VIA NTP, 1XRJ45 (10/100/1000 MBIT)



Transmission rate	
Transfer rate	
• at the 1st interface	10 1000 Mbit/s
Interferen	
Interfaces	
Number of interfaces / acc. to Industrial Ethernet	1
Number of electrical connections	
• at the 1st interface / acc. to Industrial Ethernet	1
Type of electrical connection	
• at the 1st interface / acc. to Industrial Ethernet	RJ45 port
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	DC
Supply voltage / 1 / from backplane bus	15 V
Relative symmetrical tolerance / at DC	
● at 15 V	3 %
Consumed current	
• from backplane bus / at DC / at 15 V / typical	0.35 A
Power loss [W]	5.3 W

Permitted ambient conditions				
Ambient temperature				
• for vertical installation / during operation	0 40 °C			
for horizontally arranged busbars / during	0 60 °C			
operation				
during storage	-40 +70 °C			
during transport	-40 +70 °C			
Relative humidity / at 25 °C / without condensation /	95 %			
during operation / maximum				
Protection class IP	IP20			
Design, dimensions and weight				
Module format	Compact module S7-1500 single width			
Width	35 mm			
Height	142 mm			
Depth	129 mm			
Net weight	0.35 kg			
Mounting type				
• S7-1500 rail mounting	Yes			
Product properties, functions, components / genera	l			
Number of units				
• per CPU / maximum	8			
• Note	depending on CPU type			
Performance data / open communication				
Number of possible connections / for open				
communication				
by means of T blocks / maximum	118; depending on the system upper limit			
Amount of data				
 as user data per ISO on TCP connection / for 	65536 byte			
open communication / by means of T blocks /				
maximum				
Number of Multicast stations	118			
Performance data / S7 communication				
Number of possible connections / for S7				
communication				
■ maximum	118			
Note	depending on the system upper limit			
Performance data / multi-protocol mode				
Number of active connections / with multi-protocol mode	118			
moue				
Performance data / IT functions				
Number of possible connections				

as client / by means of FTP / maximum	32
as server / by means of FTP / maximum	16
• as server / by means of HTTP / maximum	4
• as e-mail client / maximum	1
Amount of data / as user data for email / maximum	64 Kibyte

Performance data / telecontrol	
Protocol / is supported	
• TCP/IP	Yes
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• DCP	Yes
• LLDP	No
Configuration software	
• required	STEP 7 Professional V12 (TIA Portal) or higher
Identification & maintenance function	
 I&M0 - device-specific information 	Yes
 I&M1 – higher-level designation/location designation 	Yes

Product functions / Diagnosis	
Product function / Web-based diagnostics	Yes; yes, via S7-1500 CPU

Product functions / Routing	
Product function	
Static IP routing	Yes
 Static IP routing IPv6 	No
 dynamic IP routing 	No
 dynamic IP routing IPv6 	No
Protocol / is supported	
• RIP v1	No
• RIPv2	No
 RIPnG for IPv6 	No
• OSPFv2	No
OSPFv3 for IPv6	No
• VRRP	No
 VRRP for IPv6 	No
• BGP	No
• PPP	No
● PPoE via DSL	No

Product functions / Security	
Firewall version	stateful inspection

Product function / with VPN connection	IPSec			
Type of encryption algorithms / with VPN connection	AES-256, AES-192, AES-128, 3DES-168, DES-56			
Type of authentication procedure / with VPN connection	Preshared key (PSK), X.509v3 certificates			
Type of hashing algorithms / with VPN connection	MD5, SHA-1			
Number of possible connections / with VPN connection	16			
Product function				
 password protection for Web applications 	No			
ACL - IP-based	No			
 ACL - IP-based for PLC/routing 	No			
switch-off of non-required services	Yes			
 Blocking of communication via physical ports 	No			
 log file for unauthorized access 	Yes			

Product functions / Time	
Product function / SICLOCK support	Yes
Product function / pass on time synchronization	Yes
Protocol / is supported	
• NTP	Yes

nte			

• to website: Selector SIMATIC NET **SELECTION TOOL**

• to website: Industrial communication

• to website: Industry Mall

• to website: Information and Download Center

• to website: Image database

• to website: CAx Download Manager • to website: Industry Online Support

http://www.siemens.com/snst

http://www.siemens.com/simatic-net

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

12/09/2016