

PB1113	
Pressure transmitter	
Suitable for strong electromagnetic interference environment	
Tube connection: G1/4 internal thread	
Analog output	
Measuring range 0...200bar	
Application	Pressure: corresponding pressure Liquid and gas
Electric design	DC
Output	4...20mA analog
Operating voltage [V]	8...36 DC
Reverse polarity protection	Yes
Overload protection	Yes
Analog output	4...20mA
Loading for analog output [Ohm]	Maximum(Ub-8V) x 50 ;500,if UB=24V
Pressure rating [bar]	4
Min. bursting pressure [bar]	7
Calibrated atmospheric pressure	Standard atmospheric pressure
Accuracy / Deviation [% of the final value]	< ±1
Characteristics deviation	
Repeatability	<0.5
Max. temperature coefficient of zero point	0.5
Max. temperature coefficient of measuring	0.5
Analog output response time [ms]	3
Environmental temperature [°C]	-25...80
Medium temperature [°C]	-25...80
Storage temperature [°C]	-40...100
Calibrated temperature	25±0.5
Protection classification	IP67
Insulation resistance [MΩ]	>100(500 VDC)
Dimension	

Shock resistance [g]	50
Vibration resistance [g]	20
Housing material	Stainless steel (S304);Aluminum alloy,
Medium contacting material	S304;Ceramic; FPM (Viton)
Connection	M12 socket
Connection picture	
Core color	 

**ema**

ema Electronics Ltd.

Website: [www.ema-electronic.com](http://www.ema-electronic.com)

E-Mail: [info@ema-electronic.com](mailto:info@ema-electronic.com)