

SIMATIC ET 200AL, DIQ 4+DQ 4X24VDC/0,5A, 8XM8, DEGREE OF PROTECTION IP67



General information	
Product type designation	DIQ 4+DQ 4X24VDC/0.5A, 8xM8
HW functional status	E01
Firmware version	V1.0.x
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	STEP 7 V13 SP1 or higher
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	From V5.5 SP4 Hotfix 3
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	GSD as of Revision 5
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	GSDML V2.3.1
Supply voltage	
Load voltage 1L+	
<ul style="list-style-type: none"> <li>Rated value (DC)</li> </ul>	24 V
<ul style="list-style-type: none"> <li>permissible range, lower limit (DC)</li> </ul>	20.4 V
<ul style="list-style-type: none"> <li>permissible range, upper limit (DC)</li> </ul>	28.8 V

• Reverse polarity protection	Yes; Against destruction; encoder power supply outputs applied with reversed polarity, loads pick up
<b>Load voltage 2L+</b>	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes; against destruction; load increasing
<b>Input current</b>	
Current consumption (rated value)	40 mA; without load
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
<b>Encoder supply</b>	
Number of outputs	4
<b>24 V encoder supply</b>	
• Short-circuit protection	Yes; per module, electronic
• Output current, max.	0.7 A; Summenstrom aller Geber
<b>Power loss</b>	
Power loss, typ.	2.5 W
<b>Digital inputs</b>	
Number of digital inputs	4; Parameterizable as DIQ
Input characteristic curve in accordance with IEC 61131, type 3	Yes
<b>Number of simultaneously controllable inputs</b>	
all mounting positions	
— up to 55 °C, max.	4
<b>Input voltage</b>	
• Type of input voltage	DC
• Rated value (DC)	24 V
• for signal "0"	-3 to +5V
• for signal "1"	+11 to +30V
<b>Input current</b>	
• for signal "1", typ.	3.2 mA
<b>Input delay (for rated value of input voltage)</b>	
for standard inputs	
— at "0" to "1", min.	1.2 ms
— at "0" to "1", max.	4.8 ms
— at "1" to "0", min.	1.2 ms
— at "1" to "0", max.	4.8 ms
<b>Cable length</b>	
• unshielded, max.	30 m

Digital outputs	
Number of digital outputs	8; 4 DQ fixed, 4 DIQ parameterizable
<ul style="list-style-type: none"> <li>in groups of</li> </ul>	4; 2 load groups for 4 outputs each
Short-circuit protection	Yes; per channel, electronic
<ul style="list-style-type: none"> <li>Response threshold, typ.</li> </ul>	0,7 A
Limitation of inductive shutdown voltage to	2L+ (-47 V)
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	5 W
Load resistance range	
<ul style="list-style-type: none"> <li>lower limit</li> </ul>	48 $\Omega$
<ul style="list-style-type: none"> <li>upper limit</li> </ul>	4 k $\Omega$
Output voltage	
<ul style="list-style-type: none"> <li>for signal "1", min.</li> </ul>	L+ (-0.8 V)
Output current	
<ul style="list-style-type: none"> <li>for signal "1" rated value</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>for signal "0" residual current, max.</li> </ul>	0.5 mA
Switching frequency	
<ul style="list-style-type: none"> <li>with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>with inductive load, max.</li> </ul>	0.5 Hz
<ul style="list-style-type: none"> <li>on lamp load, max.</li> </ul>	1 Hz
Total current of the outputs	
<ul style="list-style-type: none"> <li>Current per group, max.</li> </ul>	2 A
Cable length	
<ul style="list-style-type: none"> <li>unshielded, max.</li> </ul>	30 m
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> <li>2-wire sensor</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul>	1.5 mA
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; channel by channel, parameterizable
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes; Parameterizable
Diagnostic messages	
<ul style="list-style-type: none"> <li>Short-circuit</li> </ul>	Yes; Outputs to M; encoder supply to M; module by module
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>Channel status display</li> </ul>	Yes; Green LED
<ul style="list-style-type: none"> <li>for module diagnostics</li> </ul>	Yes; Green/red LED
<ul style="list-style-type: none"> <li>For load voltage monitoring</li> </ul>	Yes; Green LED
Potential separation	
between the load voltages	Yes

Potential separation channels	
<ul style="list-style-type: none"> <li>• between the channels, in groups of</li> </ul>	4; DIQ channels are isolated from DQ channels
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• between the channels and the power supply of the electronics</li> </ul>	No; DIQ channels are non-isolated and DQ channels are isolated from supply voltage 1L+

Isolation	
Isolation tested with	707 V DC (type test)

Degree and class of protection	
Degree of protection acc. to EN 60529	
<ul style="list-style-type: none"> <li>• IP65</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• IP67</li> </ul>	Yes

Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>• min.</li> </ul>	-25 °C
<ul style="list-style-type: none"> <li>• max.</li> </ul>	55 °C

Connection method	
Inputs/outputs	M8, 3-pole
Power supply	M8, 4-pole
ET-Connection	
<ul style="list-style-type: none"> <li>• ET-Connection</li> </ul>	M8, 4-pin, shielded

Dimensions	
Width	30 mm
Height	159 mm
Depth	40 mm

Weights	
Weight, approx.	145 g
<b>last modified:</b>	09.04.2016