

SIMATIC ET 200MP. PROFIBUS INTERFACE MODULE IM155-5
DP ST FOR MAX. 12 S7-1500 MODULES



General information	
Product type designation	IM 155-5 DP ST
HW functional status	FS01
Firmware version	V2.0.0
Vendor identification (VendorID)	81AAh
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V13 / V13
• STEP 7 configurable/integrated as of version	V5.5 SP3 / -
• PROFIBUS as of GSD version/GSD revision	V1.0 / V5.1
Configuration control	
via user data	No
via dataset	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V

permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Short-circuit protection	Yes
Mains buffering	
• Mains/voltage failure stored energy time	5 ms

Input current	
Current consumption (rated value)	0.2 A; at 24 V DC and without load
Current consumption, max.	1.2 A; at 20.4 V DC and max. load
Inrush current, max.	4 A
I^2t	0.09 A ² ·s
from interface 5 V DC, max.	80 mA

Power	
Infeed power to the backplane bus	14 W

Power loss	
Power loss, typ.	4 W

Address area	
Address space per module	
• Address space per module, max.	32 byte; per input / output
Address space per station	
• Address space per station, max.	244 byte; per input / output

Hardware configuration	
Integrated power supply	Yes
System power supply can be plugged in to left of IM	No
Number of permissible power segments	1
Rack	
• Modules per rack, max.	12; I/O modules

Interfaces	
Number of PROFIBUS interfaces	1

1. Interface	
Interface types	
• RS 485	Yes
Functionality	
• PROFIBUS DP slave	Yes

Interface types	
RS 485	
• Transmission rate, max.	12 Mbit/s

Protocols	
PROFIBUS	

Services	
— SYNC capability	Yes
— FREEZE capability	Yes
— DPV1	Yes

Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No

Interrupts/diagnostics/status information	
Status indicator	Yes
Alarms	Yes
Diagnostic functions	Yes
Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• MAINT LED	Yes; yellow LED
• Connection display DP	Yes; Green LED

Potential separation	
between backplane bus and electronics	No
between PROFIBUS DP and all other circuit components	Yes
between supply and all other circuits	No

Isolation	
Isolation tested with	707 V DC (type test)

Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C

Connection method	
ET-Connection	
• via BU/BA Send	No

Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm

Weights	
Weight, approx.	360 g

last modified: 12/19/2016