

SIMATIC S7-1500, CM PTP RS422/485 BA COMMUNICATION MODULE FOR SERIAL CONNECTION RS422, RS485 FREEPORT, 3964(R), USS, 19200 KBIT/S, 15-PIN SUB-D FEMALE CONNECTOR



Figure similar

General information	
Product type designation	CM PtP RS422/485 BA
Product function	
• I&M data	Yes; I&M 0
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	V12 / V12
• STEP 7 configurable/integrated as of version	V5.5 SP2 with GSD file
• PROFIBUS as of GSD version/GSD revision	- / -
• PROFINET as of GSD version/GSD revision	V2.3
Installation type/mounting	
Rail mounting possible	Yes; S7-1500 mounting rail
Input current	
Current consumption (rated value)	33 mA; From the backplane bus
Power	
Power available from the backplane bus	0.65 W

Power loss	
Power loss, typ.	0.6 W
Address area	
Occupied address area	
• Inputs	8 byte
1. Interface	
Interface types	
• RS 485	Yes
• RS 422	Yes
Interface types	
RS 485	
• Transmission rate, max.	19.2 kbit/s
• Cable length, max.	1 200 m
RS 422	
• Transmission rate, max.	19.2 kbit/s
• Cable length, max.	1 200 m
• 4-wire full duplex connection	Yes
• 4-wire multipoint connection	No
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	1 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
Telegram buffer	
• Buffer memory for telegrams	2 kbyte
• Number of telegrams which can be buffered	255
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	No
Diagnostic messages	
• Wire-break	Yes

Diagnostics indication LED	
• RUN LED	Yes; Green LED
• ERROR LED	Yes; Red LED
• Receive RxD	Yes; yellow LED
• Transmit TxD	Yes; yellow LED

Potential separation	
between backplane bus and interface	Yes

Isolation	
Isolation tested with	707 V DC (type test)

Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	0 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	0 °C
• vertical installation, max.	40 °C

Decentralized operation	
to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes
Fast Startup supported	Yes

Dimensions	
Width	35 mm
Height	147 mm
Depth	127 mm

Weights	
Weight, approx.	0.22 kg
last modified:	12/19/2016