

SIMATIC S7-1500, FRONTCONNECTOR PUSH-IN TYPE, 40PIN, FOR 35MM WIDE MODULES INCL. 4 JUMPERS AND CABLE STRAP



Connection method	
Connection I/O signals	
<ul style="list-style-type: none"> <li>• Connection method</li> <li>• Number of lines per connection</li> </ul>	<p>Push-in terminal</p> <p>1; or combination of 2 conductors of up to 1.5 mm<sup>2</sup> (total) in a shared ferrule</p>
Conductor cross-section in mm <sup>2</sup>	
— Connectable cable cross-sections for massive cables, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for massive cables, min.	1.5 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, max.	1.5 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm <sup>2</sup>
Conductor cross-section acc. to AWG	

- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for massive cables, min.
- Connectable cable cross-sections for flexible cables without end sleeve, min.
- Connectable cable cross-sections for flexible cables without end sleeve, max.
- Connectable cable cross-sections for flexible cables with end sleeve, min.
- Connectable cable cross-sections for flexible cables with end sleeve, max.

24  
16  
24  
16  
24  
16

#### Wire end processing

- Stripped length of cables, min.
- Stripped length of cables, max.
- End sleeve acc. to DIN 46228 without plastic sleeve
- End sleeve acc. to DIN 46228 with plastic sleeve

8 mm  
11 mm  
Form A, 10 mm long  
Form E, 8 mm and 10 mm long

#### Mounting

- Tool

Screwdriver, conical design, 3 mm to 3.5 mm

#### Dimensions

Width	25.5 mm
Height	131 mm
Depth	37 mm

#### Weights

Weight, approx.	123 g
-----------------	-------

**last modified:** 12/12/2016