

Item Code	PR12		PR12	
Sensing mode	Through beam(Emitter)	Through beam(Receiver)	Through beam(Emitter)	Through beam(Receiver)
Sensing distance	5m (Non-adjustable)	5m (Non-adjustable)	10m (Non-adjustable)	10m (Non-adjustable)



Output	NPN NO	PR12-TM5D	PR12-TM5DNO	PR12-TM10D	PR12-TM10DNO
	NPN NC	PR12-TM5D	PR12-TM5DNC	PR12-TM10D	PR12-TM10DNC
Output	PNP NO	PR12-TM5D	PR12-TM5DPO	PR12-TM10D	PR12-TM10DPO
	PNP NC	PR12-TM5D	PR12-TM5DPC	PR12-TM10D	PR12-TM10DPC

Technical Parameter

Supply voltage	10...30 VDC	10...30 VDC	10...30 VDC	10...30 VDC
Light source	Infrared LED (880nm)	Infrared LED (880nm)	Infrared LED (880nm)	Infrared LED (880nm)
Load current	...	<200mA	...	<200mA
Voltage drop	...	<2.5V	...	<2.5V
Consumption current	<25mA	<25mA	<25mA	<25mA
Hysteresis
Repeat accuracy	<5%	<5%	<5%	<5%
Response time	...	<8.2ms	...	<8.2ms
Output indicator	Green LED	Yellow LED	Green LED	Yellow LED
Polarity protection	yes	yes	yes	yes
Surge protection	yes	yes	yes	yes
Short-circuit protection	...	yes	...	yes
Ambient temperature	-15...+55°C	-15...+55°C	-15...+55°C	-15...+55°C
Ambient moisture	35...95%	35...95%	35...95%	35...95%
Protection degree	IP67	IP67	IP67	IP67
Housing material	Nickel-copper Alloy	Nickel-copper Alloy	Nickel-copper Alloy	Nickel-copper Alloy
Connection	2m PVC Cable	2m PVC Cable	2m PVC Cable	2m PVC Cable
Certification	CE U _L	CE U _L	CE U _L	CE U _L

